

SF 50 CL



Product description

- Safety(Security) Film
- Application: Automotive, Architecture
- Thickness: 1ply 2mil
- Features:

High visibility and clear color
Safety effect for Personal life
Shatter-proof performance

Typical properties

Items	code	SF-50 CL
Visible light transmittance	vlt	86
visible light reflectance	VLR	13.09
ultraviolet rejection	UVR	95
Tensile Strength (kgf/mm ²)	T.D.	10.3
	M.D.	11.6
	T.D.	114
Elongation (%)	M.D.	78
	T.D.	47.7
	M.D.	58
Break Strength (lbs/inch)	PRL	31.1
Puncture Resistance Load(lbs)	PS	>1800
Peel Strength (gr/inch)	MP	255-265
Melting Point (°C)	4B~4H	2H<
scratch resistance		

*All of the data were evaluated by attaching a 1/8"glass in the UV/VIS spectrometer.

CONCO LTD.

O. K. Park

President / O.Gyoon Park

Date 24, June 2022y

CONCO LTD.
Tel +82 31 637 3210 Fax +82 31 632 3207
E-mail sales@conco.co.kr
Website www.conco.co.kr
130 Mado-ro, Majang-myeon, Icheon-si,
Gyeonggi-do, 17382, Republic of Korea.



SF 100 CL



Product description

- Safety(Security) Film
- Application: Automotive, Architecture
- Thickness: 1ply 4mil
- Features:

High visibility and clear color
Safety effect for Personal life
Shatter-proof performance

Typical properties

Items	code	SF-100 CL
Visible light transmittance	vlt	88.4
visible light reflectance	VLR	10.63
ultraviolet rejection	UVR	95
Tensile Strength (kgf/mm2)	T.D.	11.5
	M.D.	13.9
Elongation (%)	T.D.	88
	M.D.	73
Break Strength (lbs/inch)	T.D.	78.5
	M.D.	94
Puncture Resistance Load(lbs)	PRL	52.3
Peel Strength (gr/inch)	PS	>1800
Melting Poing ©	MP	255-265
scratch resistance	4B~4H	2H<

*All of the data were evaluated by attaching a 1/8"glass in the UV/VIS spectrometer.

CONCO LTD.
O. K. Park
President / O.Gyoon Park

Date 24, June 2022y

CONCO LTD.
Tel +82 31 637 3210 Fax +82 31 632 3207
E-mail sales@conco.co.kr
Website www.conco.co.kr
130 Mado-ro, Majang-myeon, Icheon-si,
Gyeonggi-do, 17382, Republic of Korea.



SF 175 CL



Product description

- Safety(Security) Film
- Application: Automotive, Architecture
- Thickness: 1ply 7mil
- Features:

High visibility and clear color
Safety effect for Personal life
Shatter-proof performance

Typical properties

Items	code	SF-175 CL
Visible light transmittance	VLT	83
visible light reflectance	VLR	16.2
ultraviolet rejection	UVR	95
Tensile Strength (kgf/mm2)	T.D.	12.3
	M.D.	14.2
	T.D.	107
Elongation (%)	M.D.	62
	T.D.	158
	M.D.	176
Break Strength (lbs/inch)	PRL	87.2
	PS	>1800
Puncture Resistance Load(lbs)	MP	255-265
Peel Strength (gr/inch)	MP	255-265
Melting Poing ©	MP	255-265
scratch resistance	4B~4H	2H<

*All of the data were evaluated by attaching a 1/8"glass in the UV/VIS spectrometer.

CONCO LTD.

O. K. Park

President / O Gyoon Park

Date 24, June 2022y

CONCO LTD.
Tel +82 31 637 3210 Fax +82 31 632 3207
E-mail sales@conco.co.kr
Website www.conco.co.kr
130 Mado-ro, Majang-myeon, Icheon-si,
Gyeonggi-do, 17382, Republic of Korea.



SF 300 CL



Product description

- Safety(Security) Film
- Application: Automotive, Architecture
- Thickness: 2ply 12mil
- Features:

High visibility and clear color
Safety effect for Personal life
Shatter-proof performance

Typical properties

Items	code	SF-300 CL
Visible light transmittance	VLT	83
visible light reflectance	VLR	16.8
ultraviolet rejection	UVR	95
Tensile Strength (kgf/mm2)	T.D.	12.5
	M.D.	19.5
	T.D.	99
Elongation (%)	M.D.	67
	T.D.	251
Break Strength (lbs/inch)	M.D.	298
Puncture Resistance Load(lbs)	PRL	142.5
Peel Strength (gr/inch)	PS	>1800
Melting Poing ©	MP	255-265
scratch resistance	4B~4H	2H<

*All of the data were evaluated by attaching a 1/8"glass in the UV/VIS spectrometer.

CONCO LTD.
O. K. Park
President / O.Gyoon Park
Date 24, June 2022y

CONCO LTD.
Tel +82 31 637 3210 Fax +82 31 632 3207
E-mail sales@conco.co.kr
Website www.conco.co.kr
130 Mado-ro, Majang-myeon, Icheon-si,
Gyeonggi-do, 17382, Republic of Korea.

